PCT

990396

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

INTERCEPTION OF THE PROPERTY O					
(51) International Patent Classification 7:		(11) International Publication Number:	WO 00/51203		
H01Q 9/16	A1	(43) International Publication Date:	31 August 2000 (31.08.00)		

FI

(21) International Application Number: PCT/FI00/00139
(22) International Filing Date: 22 February 2000 (22.02.00)

ES, KE, MD (30) Priority Data: (81) Designs BR, ES, KE, MD SD,

24 February 1999 (24.02.99)

(71) Applicant (for all designated States except US): NOKIA NETWORKS OY [FI/FI]; P.O. Box 300, Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventor; and
 (75) Inventor/Applicant (for US only): MOILANEN, Mikko [FI/FI]; Salontaantie 10, FIN-24800 Halikko (FI).

(74) Agent: HEINÄNEN OY; Annankatu 31-33 C, FIN-00100 Helsinki (FI). (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.


Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Finnish).

(54) Title: ANTENNA RADIATOR

(57) Abstract

Antenna radiator, consisting of two plate-like or film-like parts (1, 2) connected by their foot ends (11) to each other and to the supply connection of the antenna. To reduce especially current and voltage losses, the radiator parts are substantially wider at the foot (11) than at the tip (12).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia -	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of Ameri
	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CA		JР	Japan	NE	Niger	VN	Viet Nam
CF	Central African Republic	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CG	Congo Switzerland	KG	•	NO	Norway	zw	Zimbabwe
CH		KP	Kyrgyzstan Democratic People's	NZ	New Zealand	٥.,	2
CI	Côte d'Ivoire	KP		PL	Poland		
CM	Cameroon	***	Republic of Korea	PT	Portugal		
CN	China	KR	Republic of Korea	RO	Romania		
CU	Cuba	KZ	Kazakstan		•		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

ANTENNA RADIATOR

5

10

25

35

The present invention relates to an antenna radiator consisting of two plate-like or film-like parts connected by their foot ends to each other and also to the supply connection of the antenna.

For instance, the base transceiver stations of mobile telephone systems use dipole antenna systems comprising dipole antennas adapted for one or more frequency ranges, e.g. 900 MHz and 1800 MHz. The antennas have relatively narrow radiators which consist of two parts extending to both sides of the supply point of the antenna. The antennas have been made e.g. by etching on a fiberglass circuit plate. The radiators of the antennas are relatively narrow.

Due to the high frequencies used in mobile telephone systems, the circuit plate on which the antenna construction has been etched causes dissipation. The dissipation is mainly due to a large current flowing at the foot of the radiator parts and to voltage losses occurring at the tips of the radiator parts. A drawback with present antennas is the magnitude of dissipation, which is a result of especially the fact that the radiator parts are narrow at the foot.

The object of the present invention is to eliminate the drawbacks of priorart solutions and achieve a radiator structure especially applicable for use in base stations of mobile telephone systems. The antenna radiator of the invention is characterized in that, especially to reduce current and voltages losses, the radiator parts are substantially wider at the foot than at the tip.

An embodiment of the invention is characterized in that the radiator parts taper from the foot towards the tip.

When a radiator according to the invention is used, dissipation caused by the circuit plate is reduced because the wide foot part reduces the losses due to the current flowing in the foot. In addition, due to their narrow 10

15

20

35

shape, the tips have a small contact area, thus producing only small voltage losses. Therefore, a good radiation efficiency is achieved.

In the following, the invention will be described in detail by the aid of an example with reference to the attached drawing, which presents an antenna with a radiator according to the invention, suited for use e.g. in a base transceiver station of the 900 MHz mobile telephone network.

The dipole antenna presented in the figure comprises a film-like dipole radiator of electrically conductive material, consisting of two parts, an upper and a lower part 1, 2. The parts are connected together by a narrow metal strip 3. Placed behind the radiator 1, 2 is a reflector 4, whose length somewhat exceeds the height of the radiator. The radiator 1, 2 and the strip 3 have been etched on a fiberglass circuit plate 5. The antenna is connected by a connecting cable 6 from the supply point at the middle of the strip 3 to the receiver-transmitter apparatus of a base transceiver station.

The radiator parts 1, 2 are of a triangular shape and symmetric with respect to each other so that the upper triangle points upward and the lower triangle 2 downward. Thus, each part 1, 2 tapers linearly from the foot end 11 towards the tip 12. The side 13 in the direction of the main beam is inclined while the side 14 next to the reflector 4 is upright.

In the radiator of the invention, the current density is significantly smaller than in prior-art solutions, especially at the foot 11 of the radiator parts 1, 2, where the current is largest, thanks to the width of the foot end structure. As the current is diminished toward the tip, the radiator part 1 tapers linearly, so that the tip 12 of the radiator, which is the most sensitive area of the radiator in respect of the operation of the antenna, is narrow. In addition, the tip 12 has a blunt shape to avoid interference.

It is obvious to a person skilled in the art that different embodiments of the invention are not restricted to the example described above, but that they may be varied within the scope of the claims presented below.

CLAIMS

15

25

- 1. Antenna radiator, consisting of two plate-like or film-like parts (1, 2) connected by their foot ends (11) to each other and to the supply connection of the antenna, c h a r a c t e r i z e d in that, to reduce especially current and voltage losses, the radiator parts are substantially wider at the foot (11) than at the tip (12).
- 2. Radiator as defined in claim 1, c h a r a c t e r i z e d in that the radiator parts (1,2) taper from the foot (11) toward the tip (12).
 - 3. Radiator as defined in claim 2, c h a r a c t e r i z e d in that the radiator parts (1,2) taper substantially linearly from the foot (11) toward the tip (12).
- 4. Radiator as defined in claim 1 in an antenna provided with a reflector (4) behind the radiator, c h a r a c t e r i z e d in that the edge (13) of the radiator part on the side facing in the direction of radiation is straight while the edge (14) opposite to the direction of radiation is inclined, or vice versa.
 - 5. Radiator as defined in claim 1, c h a r a c t e r i z e d in that the radiator parts (1,2) are connected to each other via a narrow strip-like connecting part (3), the supply connection of the antenna being fitted in conjunction with it.
 - 6. Radiator as defined in claim 1, c h a r a c t e r i z e d in that the radiator has been fitted on a circuit plate (5).

WO 00/51203 PCT/FI00/00139

1/1




FIG. 1

INTERNATIONAL SEARCH REPORT

International application No. PCT/FI 00/00139

	·					
A. CLASS	SIFICATION OF SUBJECT MATTER					
IPC7: H010 9/16 According to International Patent Classification (IPC) or to both national classification and IPC						
	OS SEARCHED					
Minimum d	ocumentation searched (classification system followed by	classification symbols)				
IPC7: F						
Documentat	tion searched other than minimum documentation to the	extent that such documents are included in	n the fields searched			
	-I,NO classes as above					
Electronic d	ata base consulted during the international search (name	of data base and, where practicable, search	n terms used)			
C. DOCU	MENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where app	propriate, of the relevant passages	Relevant to claim No.			
A	US 5293175 A (DALE L. HEMMIE ETE 8 March 1994 (08.03.94), col	1-6				
	line 19 - line 48, figures 1-2,4-5					
A	EP 0889543 A1 (SONY INTERNATIONAL (EUROPE) GMBH), 1-6 7 January 1999 (07.01.99), column 6,					
line 58 - column 7, line 14; column 9, line 57 - column 10, line 26, figures 2,6						
	Time 57 - Column 10, Time 20	, 11gares 2,0				
٠						
Further documents are listed in the continuation of Box C. X See patent family armex.						
* Special categories of cited documents: "I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention						
to be of particular relevance "F" erlier document but published on or after the international filing date "X" document of particular relevance; the claimed invention cannot be						
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other						
special reason (as specified) "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination						
"P" document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family						
Date of the actual completion of the international search Date of mailing of the international search report						
19 .11.	2 1 -07- 2000					
19 July 2000 Name and mailing address of the ISA/ Authorized officer						
	Patent Office					
	, S-102 42 STOCKHOLM No. + 46 8 666 02 86	Rune Bengtsson/AE Telephone No. +46 8 782 25 00				

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No. 02/12/99 | PCT/FI 00/00139

	Patent document cited in search repo		Publication date		Patent family member(s)	Publication date
U	5 5293175	Α	08/03/94	US	5229782 A	20/07/93
El	0889543	A1	07/01/99	CA	2241128 A	30/12/98

Form PCT/ISA/210 (patent family annex) (July 1992)